

BiAMP - 1320



Bi - Directional RF Amplifier

The BiAMP-1320 is a UHF (1350 MHz to 1390 MHz) bi-directional RF amplifier. The BiAMP-1320 offers high speed switching between transmit and receive with excellent noise figure, automatic gain control and automatic transmit gain control.

Features

- 12 dB receive gain
- Automatic TX gain control
- Instantaneously automatic RX/TX switching
- Extremely low noise figure
- Cast aluminum construction
- Receive band pass filter
- TX/RX LEDs
- Heavy duty N-Female connectors
- Industrial temperature specification
- Light weight
- Low profile design



Applications

- Increase the range of MHX/Spectra/IP1320 transceivers

Restricted Sale to Military, Government and Export to Qualifying Customers Outside Canada and USA.

Specifications

Frequency Band	1350 - 1390 MHz	Impedance	50 Ω
Receive Gain	11 dB \pm 1 dB	Supply Voltage	12 VDC to 13.5VDC @ 2.5 Amps
Max Output Power	10 W	Connectors	N female
Transmit Level	15 dBm to 26 dBm	Weight	Approx. 1.02lbs (465g)
Noise Figure	2.5 dB \pm 0.5 dB	Dimensions	Approx. 5.875" x 2.5" x 1.438" (150mm x 63.5mm x 36.52mm)
RX/TX Switching	100 μ s		

Contact Information

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762

Copyright 2010 Microhard Systems Inc.
Specifications subject to change without notice.



www.microhardcorp.com