

DDL840 Amplifier



Digital Data Link 840 - 845 MHz 10W Linear (30W FM) Amplifier

The DDL840 Amplifier is a 10W Linear (30W FM) amplifier, designed for use in the 840-845 MHz frequency range. The DDL840 Amplifier offers a compact, rugged design, featuring high speed Tx/Rx switching.

Features

- Rx Band-pass filtering
- Automatic Tx/Rx switching
- External Tx-Rx triggering, if required
- Overvoltage protection on all ports
- Tx/Rx LEDs
- Light weight
- Compact & rugged design



Applications

- Increase the range of Microhard 840 - 845 MHz transceivers

COTS - No Export Permit Required

Specifications

Frequency	840 - 845 MHz	
Tx Power Gain	14-15 dB Typical	
Tx O/P Power	<u>Modulation</u>	<u>Power</u>
	P1dB	>35W
	GMSK	30W
	QAM 64	8W
	QAM 16	10W
	QPSK	13W
Rx Gain	8 dB \pm 1 dB	

Rx/Tx Switching	1 μ s Typical
Impedance	50 Ω
DC Supply Voltage	24-30 VDC
Connectors	Female SMA (RF in, RF out) Female Quick Connect 3pin (Power)
Weight	Approx. 275g
Dimensions	Approx. 3.3" x 3.0" x 0.95" (85mm x 75mm x 24mm) Approx. 4.1" x 3.4" x 0.95" (Inc. Connectors)

Contact Information

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762

Copyright 2017 Microhard Systems Inc.
Specifications subject to change without notice.

