

Nano IP Series - IPn1320



Miniature OEM Wireless Ethernet/Serial/USB Gateway

The Nano IP Series adds Ethernet capability to the miniature, yet powerful Nano platform. This incredibly small Ethernet Bridge and Serial Gateway provides robust wireless communication of simultaneous serial data and IP/Ethernet packets to extend serial data and IP networks.

Applications

- Unmanned Aerial Vehicles
- Unmanned Ground Vehicles
- Drones
- Wireless Video, Telemetry
- Research and Development
- Robotics

Microhard Systems Inc.'s proprietary radio technology excels in the most demanding RF and physical environments.



Weights only 25grams!

World's Smallest Ethernet/Serial/USB Gateway!

The Nano IP platform is the smallest form factor (2" x 1.25" x .5", weighing only 25 grams) available which offers a full Ethernet/Serial/USB bridge and routing functionality. The Nano IP OEM module can be directly integrated into OEM systems or applications using a variety of interface options. With the LAN out interface ready to wire directly to CAT5 cable OEMs can integrate this unit quickly and efficiently. The Nano IP Series also features flexible maintenance utilities, secure firewall features and network management facilities. Robust Frequency Hopping with excellent receiver sensitivity and interference rejection allow for long range, high speed communications.

Features of the Nano IP Series

- Low Power Consumption
 - Up to 1.2 Mbps Wireless Link Rate*
 - Master, Slave, Repeater operation in a single unit
 - HV Option provides a quick wiring solution with Ethernet and Serial Levels and Power (7-30 VDC)
 - 2 Serial Com Ports, 1 USB Port, and 1 Ethernet Port
 - Supports Point-to-Point, Point-to-Multipoint, Repeater, Peer-to-Peer
 - Adjustable transmit power (100mW - 1W)
 - Radius Server Support
 - Full VLAN Support (for separate management and Data networking)
 - User interface through local console, telnet, and web browser
 - Network management capability with SNMP V1, V2, V3
 - Local and remote wireless firmware upgrading through FTP
 - QoS Routing on Serial, IP, or Logic Ports
- * For Faster Link Rates Contact Microhard

Interface Options

Enclosed Solution



Motherboard Solution



HV Solution



◆ VLAN ◆ RADIUS ◆ QoS ◆ HTTPS ◆ USB ◆ Firewall

IPn1320

Specifications



Frequency	1350 - 1390 MHz* *Contact Microhard Systems for additional frequencies	Input Voltage	OEM Enclosed Interface Card	3.3VDC Nominal (+/- 0.3V) 7-30VDC 7-30VDC
Spread Method	Frequency Hopping / DTS	Power Consumption (Typical with n920F @ 12V with Motherboard)		Sleep: < 1mA Idle: 35mA Rx: 110mA to 145mA Tx: 350mA to 500mA
Link Rate	Up to 1.2Mbps (See Order Options)	Connectors:	OEM Antenna Data Enclosed Antenna Data	OEM - MMCX OEM - 60 Pin OEM Header x2 RP-TNC Female Bulkhead RJ-45 (Ethernet) Female DB9 Mini-USB
Error Detection	32 bits of CRC, ARQ	Environmental	Temperature Humidity	-40°F to 170°F (-40°C to +75°C) 5-95%, noncondensing
Encryption	128-bit WEP/WPA (Canada & USA only. NOT AVAILABLE for export, see -AES option)	Weight (Including Radio)	OEM Enclosed w/ Interface Board	Approx. 25 grams Approx. 240 grams Approx. 70 grams (No Conn. 50g)
Range	Up to 30+ miles (50+ km) @ 1.2Mbps Up to 60+ miles (100+ km) @ 172kbps	Dimensions	OEM Enclosed	Approx. 1.25" x 2.0" x .50" (32mm x 51mm x 13mm) Approx. 2.25" x 3.75" x 1.75" (57mm x 95mm x 45mm)
Sensitivity	-108dBm @ 172kbps link rate -106dBm @ 230kbps link rate -97dBm @ 1.2Mbps link rate	Sale Restriction		Restricted Sale to Military, Government and Export. Export Means Qualifying Customers Outside Canada and USA.
Output Power	100mW - 1W (20-30dBm)	Order Options		
Serial Interface	RS232, RS485, RS422	-AES		128/256-bit AES Encryption, Secure Shell, HTTPS (Canada & USA only. NOT AVAILABLE for export)
Serial Baud Rate	300bps to 921kbps	IPn1320F		115kbps - 230kbps
USB	USB 2.0 USB Console Port USB to Serial Data Routing USB to Ethernet Data Routing	IPn1320T		1.2Mbps
Ethernet	10/100 BaseT, Auto - MDI/X IEEE 802.3			
Network Protocols	TCP, UDP, TCP/IP, TFTP, ARP, ICMP, DHCP, HTTP, HTTPS*, SSH*, SNMP, FTP, DNS, Serial over IP, QoS (* Only available in -AES)			
Operating Modes	Point-to-Point, Point-to-Multipoint, Store & Forward Repeater, Peer-to-Peer			
Management	Local Serial Port Console, Telnet, WebUI, SNMP, FTP & Wireless Upgrade, RADIUS authentication, VLAN			
Diagnostics	Battery Voltage, Temperature, RSSI, and remote diagnostics			
Rejection	Excellent strong signal interference & rejection characteristics			
Input IP3 (Antenna Connector)	+12 dBm			

Contact Information

Copyright 2010 Microhard Systems Inc.
Specifications subject to change without notice.

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762



www.microhardcorp.com