

DDL1350 Amplifier



Digital Data Link 10W Linear Amplifier

The DDL1350 Amplifier is a 10W 1350 MHz linear amplifier, designed for Digital Data Link applications. The DDL1350 Amplifier offers a compact, rugged design, featuring high speed automatic Tx/Rx switching.

Features

- Rx Band-pass filtering
- Automatic Tx/Rx switching
- External Tx-Rx triggering, if required
- Overvoltage protection on all ports
- Tx/Rx LEDs
- Light weight
- Compact & rugged design



Applications

- Increase the range of pDDL & IPnDDL transceivers

COTS - No Export Permit Required

Specifications

Frequency	1350 - 1390 MHz		Rx/Tx Switching	1 μ s Typical
Tx Power Gain	12-13 dB Typical		Impedance	50 Ω
Tx O/P Power	<u>Modulation</u>	<u>Power</u>	DC Supply Voltage	24-30 VDC
	P1dB	>25W	Connectors	Female SMA (RF in, RF out) Female Circular Bayonet 3pin (DC Power)
	QAM 64	8W	Weight	Approx. 275g
	QAM 16	10W	Dimensions	Approx. 3.3" x 3.0" x 0.95" (85mm x 75mm x 24mm) Approx. 4.1" x 3.4" x 0.95" (Inc. Connectors)
Rx Gain	8 dB \pm 1 dB			

Contact Information

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762

Copyright 2018 Microhard Systems Inc.
Specifications subject to change without notice.

