

LTE CAT M1/NB2-IoT Gateway

The LTECube-CATM-G2 was engineered specifically for the small size, low cost, and low power requirements of the IoT & M2M applications that are surging across the globe. The LTECube-CATM-G2 provides robust and reliable LTE Category M1/NB2-IoT connections with upload speeds up to 1119kbps and downloads of up to 588kbps. The LTECube-CATM-G2 features Ethernet, USB, and VPN/GRE Tunneling Capabilities all while retaining low power consumption.

LTE CAT M1

NB2-IoT

Low Cost!

Optional WIFI

IPv6 & IPv4 Support

PoE (802.3af)

LTE³-CATM-G2



Only 1.75" x 1.75" x 1.35"!

Features

- Robust & Reliable LTE CATM Operation
- Engineered for IoT Applications
- Low Cost & Ultra Low Power Consumption
- Up to 1119 kbps Upload / 588 kbps Download
- Data Usage & Systems Alerts (Email, SMS)
- Firewall with ACL Security, DMZ & Port Forwarding
- IPSec, GRE / VPN Tunneling
- 10/100 Ethernet
- Optional Enterprise Class WiFi (more than 200 clients)
- High Power 1W WiFi (Long Range)
- Full IPv6 & IPv4 Support
- MQTT Support
- Wide Operating Temperature (-40°C to +85°C)
- User interface via SSH or HTTP/HTTPS web browser
- Microhard NMS & IoT Portal Support



LTE³-CATM-G2

Specifications

Supported Bands	LTE CAT M1 / CAT NB2 / EGPRS			Management	Telnet, WebUI, SNMP V1/2/3, Wireless Upgrade (HTTP/FTP), RADIUS authentication, AT Command Interface (Telnet), Microhard NMS Support, Data Usage Alerts, SSH
	LTE-FDD: B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B25/B26(M1 Only)/B27 (M1 Only)/B28/B31*/B66/B71 (NB2 Only)/B72*/B73*/B85			Diagnostics	RSSI, Ec/No, Temperature, Remote diagnostics, Watchdog, UDP Event Reporting, SMS Alerts, Netflow
	EGPRS: 850/900/1800/1900MHz			Input Voltage	7 - 58VDC PoE (802.3af)
Cellular Data Rates*	LTE Cat M1:	Max. 588 kbps (DL) Max. 1119 kbps (UL)		Connectors:	Antenna SMA Female Data RJ-45 (Ethernet) 4 PIN Interlock (Vin) USB Micro-AB SIM Nano (4FF) 1.8 / 3.0V
	LTE Cat NB1:	Max. 32 kbps (DL) Max. 70 kbps (UL)		Environmental	Operating Temperature -40°C to +85°C -40°F to +185°F Humidity 5-95%, non-condensing
	LTE Cat NB2:	Max. 127 kbps (DL) Max. 158.5 kbps (UL)		Weight	Approx. 100 grams
	EDGE:	Max. 296 kbps (DL) Max. 236.6 kbps (UL)		Dimensions	Approx. 1.75" x 1.75" x 1.35" (45mm x 45mm x 35mm)
	GPRS:	Max. 107 kbps (DL) Max. 85.6 kbps (UL)		Approvals	FCC/IC Carrier Specific Approvals
<small>*Module Standalone Laboratory Performance</small>				Order Options	
WiFi Features <small>(WiFi Optional)</small>	802.11b/g/n (2.4 GHz)			CA-MHK119320	LTECube-CATM-G2
WiFi Performance <small>(WiFi Optional)</small>	Rate	Mode	Tx (dBm) Rx (dBm)	CA-MHK119322	LTECube-CATM-G2-Kit
	1 Mbps	b	30 -97 ± 1	CA-MHK119340	LTECube-CATM-G2-WIFI
	11 Mbps	b	30 -92 ± 1	CA-MHK119342	LTECube-CATM-G2-WIFI-Kit
	6 Mbps	g	30 -94 ± 1		
	54 Mbps	g	26 -75 ± 1		
	MCS0	n (HT20)	30 -96 ± 1		
	MCS7	n (HT20)	26 -75 ± 1		
	MCS0	n (HT40)	30 -94 ± 1		
	MCS7	n (HT40)	26 -73 ± 1		
Ethernet	10/100 BaseT, Auto - MDI/X IEEE 802.3				
USB	USB 2.0 Tethering				
SMS	SMS to/from Ethernet via Telnet SMS Alerts SMS Remote Reboots				
Carrier Connection	ICMP Keep Alive, DDNS				
Network Protocols	IPv4, IPv6, TCP, UDP, TCP/IP, ARP, ICMP, DHCP, HTTP, SNMP, FTP, DNS, Modbus Slave (TCP), MQTT				
Security	VPN, IPSec with IKE/ISAKMP; Multiple tunnel support; 3DES and up to 256-bit AES Encryption, Site to Site Tunneling, L2TP, Open VPN), GRE, HTTPS, RADIUS				
Firewall	NAT, NAT-T VPN tunneling, Port forwarding, VPN/GRE pass-through; Access control lists (IP/MAC filtering), Data origin / integrity Authentication, DMZ				

Contact Information

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762

Copyright 2022 Microhard Systems Inc.
Specifications subject to change without notice.

