

High Power (5W) OEM 1350 - 1390 MHz Wireless Modem

For the ultimate solution in design flexibility and size sensitive applications, consider the PicoPRO-1300 radio platform. Offering up to 5W of output power in the 1350-1390 MHz Band the PicoPRO-1300 offers the design flexibility, features, and performance never seen before!

Up to 345 kbps

1350 - 1390 MHz

Up to 5 Watts

Extended Temperature

Dual Serial Ports

Excellent Sensitivity



1.05" X 2.0" X 0.11"

Features

- Supports up to 345 kbps
- Up to 5W transmit power (Adjustable)
- Multi Stage, SAW Filters provide extreme noise and interference rejection
- Point-to-Point, Point-to-Multipoint, TDMA Networks
- Master, Remote & Repeater Modes
- Industrial Temperature (-55°C to +85°C)
- Low Power consumption in Sleep and Sniff modes (Future)
- 32 bits of CRC, selectable Forward Error Correction with retransmission
- Separate diagnostics port—transparent remote diagnosis and online network control
- Small Footprint (26.5 x 51 x 2.9mm | 1.05 x 2.0 x 0.11")

Enclosed Option



Specifications

Spreading Method / Modulation Scheme	Frequency Hopping (1W) Fixed Channel (5W*) Frequency Hopping w/ export permit (5W*)	Frequency 1350 to 1390 MHz (Frequency Hopping)*		
		Rate (kbps)	Sensitivity (dBm)	Bandwidth (kHz)
Forward Error Correction	Hamming, BCH, Golay, Reed-Solomon	19.2	-120	25
Error Detection	32 bits of CRC, ARQ	24.7	-119	25
Encryption	Optional (Requires Export Permit)	56	-117	60
		115.2	-114	150
Range	Up to 60 miles (100 km)	172.8	-113	180
		230.4	-111	230
Serial Interface	3.3V CMOS (OEM) RS232/485 (Selectable)	276.4	-110	230
		345	-106	400
Serial Baud Rate	300 bps to 230 kbps			
Operating Modes	Point-to-Point, Point-to-Multipoint, Store & Forward Repeater, TDMA			
Signals Interface	RSSI LEDs, Tx/Rx LEDs, Reset, Config, Wake-up, RSmode, 4 Digital Inputs/Outputs, 1 Analog Input, 1 Analog Output			
Remote Diagnostics	Battery Voltage, Temperature, RSSI, Packet Statistics			
Core Voltage	OEM	Vcc: 3.3 - 3.6 VDC Vrf: 5 VDC (4000mA)		
	Enclosed	12-30VDC		
Connectors	OEM	Antenna: UFL Data: 116 Pin SMT		
	Enclosed	Antenna: RP-SMA Female Bulkhead Data: DB9-F USB: MicroUSB Power: 4 Pin Quick Connect		
Environmental	-55°C - +85°C 5-95% humidity, non-condensing			
Weight	OEM	~ 12 grams		
	Enclosed	~225 grams		
Dimensions	OEM	Approx. 1.05" x 2.0" x .11" (26.5mm x 51mm x 2.8mm)		
	Enclosed	Approx. 3.0" x 3.5" x 1.125" (76mm x 90mm x 28.5mm)		

Order Options

PicoPRO-1300	Base Model (Fixed Freq (5W), Hopping Freq (1W), No AES Encryption)
-C1S	Fixed Freq (5W), Hopping Freq (1W), AES256**
-C2S	Fixed Freq (5W), Hopping Freq (5W), AES256**
-ENC	Enclosed Model

**AES encryption, 5W frequency hopping requires Export Permit

*Requires heat sink/cooling solution

Contact Information

Copyright 2022 Microhard Systems Inc.
Specifications subject to change without notice.

Microhard Systems Inc.
150 Country Hills Landing N.W.
Calgary, AB, Canada T3K 5P3

Email: info@microhardcorp.com
Tel: (403) 248-0028
Fax: (403) 248-2762



www.microhardcorp.com